LHP/LHD Series Check Sheet Rev. Date 7/14/17 (Note: Items below listed in **bold text** are subject to additional charge if not included in original quote) Salesman: Office Phone: INFORMATION IN THIS SECTION IS REQUIRED TO VALIDATE EQUIPMENT WARRANTY Bill To Address: Ship To Address: End User Address: End User Type: ☐ Retail Distribution .com ☐ Retail Stores ☐ Aero/Auto ☐ Transportation Consumer ☐ Pharm/Medical ☐ Developer ☐ Warehouse Food/Beverage ☐ Stock Government ☐ Farming Technology **Grocery Distribution** ☐ Grocery Retail ☐ Service ☐ Industrial Entertainment PO# Requested Ship Date: Shipping Instructions Quantity Carrier: ☐ Prepaid Flatbed Required Restraint Model Quote #: ☐ Collect Van Required Comments: Phone #: ☐ Third Party Are lifting lugs required for installation? ☐Yes ☐ No Leveler Size - REQUIRED **Leveler Capacity - REQUIRED** □ 6'W X 6'L ☐ 6'6" W X 6'L 7'W X 6'L 25,000 lbs CIR 40,000 lbs CIR □ 6'W X 8'L ☐ 6'6 W X 8'L 7'W X 8'L 35.000 lbs CIR Pit Information - REQUIRED □ New Loading Dock Area ☐ Existing Loading Dock Area Cut down in Width? Right Rear Pit Width Right Front Notes: Left Rear Left Front Pit Lenath Cut down in Length? Cut down Depth? ☐ Filler To Be Provided By Systems **Misc Metals Curb Angles Pans** Curb Angle to ship early ☐ 3 Sided Pan to ship early \square Date Required Date Required ☐ 3 Sided Pan☐ 4 Sided Pan 6 Piece Angle 4 Piece Angle/ 2 piece bumper plate Per Systems, Inc. pit detail unless otherwise noted ☐ Squaring Kit ■ Bumper Plate Weldments **Lip/Bumper Information – REQUIRED** ☐ 16" Lip Length: ☐ Max Bevel Bumpers Standard is 4-1/2" x 10" x 13" Molded Rubber ☐ 18" ☐ Reduced Lip Crown ☐ 20" Other INFORMATION IN THIS SECTION IS REQUIRED TO VALIDATE EQUIPMENT WARRANTY Dock Height Max Gross Moving Load # of Shifts Notes: Required Service Fork Truck ☐ 3 Wheel Required Service Range 4 Wheel Range Above Below 3 Wheel Offset/Standup Level Drive [**Decline Drive** Incline Drive If drive is decline / incline please explain how this is being handled. Electrical - Required Frame/Finish Information - Required Notes: Electrical Voltage and Phase ☐ Abrasive Deck **Abrasive Lip Disconnect Switch** ☐ Smooth Deck Plate **Overhead Door Buttons** ☐ Smooth Lip Plate ☐ Remote Mount Powerpack ☐ Spray Metalize ☐ Hot Dip Galvanize (Only available on units 45k and above) **Special Color Paint (Provide Sample) Optional Extras Restraint Information** Notes: **Brush Weatherseal (Rear Brush)** Restraint Engaged Interlocking (Restraint engaged or unit placed in bypass mode Rubber Weatherseal (Rear Foam)

allows leveler to operate)

Audible Alarm

Leveler Stored Interlocking (Lip Prox)
(Leveler stored allows restraint to released)

For additional loading dock, construction and safety items go to www.alliedproductsolutions.com.

Insulation

Stainless Steel Hinge Pins

Grease Fittings (Every tube)