Automatic PowerStop®Vehicle Restraint



FEATURES

- Push-button activation (115-volt, single-phase operation)
- iDock® Controls with interactive message display
- Automatic light sequence
- Low-profile, non-impact design (wall or driveway mount)
- Rig sensor bar with audible alarm
- Corrosion-resistant, zinc-plated finish

- Restraining force in excess of 32,000 lb average
- Remote power pack with translucent reservoir
- Automatically re-engages if restraint is forced down
- Sign communication package
- Designed and manufactured in the USA

Connect online with

My R_®
Enterprise

* Automatic PowerStop shown with advanced communication controls and OSLA (Outside Light Assembly).

Value Engineered
Dock Levelers



Automatic PowerStop®Vehicle Restraint

VEHICLE RESTRAINT SYSTEM

The PowerStop® is a non-impact, hydraulic vehicle restraint, available as a standalone unit or integrated with other loading dock equipment through an optional integrated control panel. The unit helps prevent unexpected trailer departure from the loading dock during the loading/unloading process.

OPERATION

Once a trailer is backed into position against the dock bumpers, the operator presses the Engage button, activating the PowerStop to rise vertically to the trailer's Rear Impact Guard (RIG), placing a stop behind the RIG and preventing the trailer from being able to pull away. The restraint maintains contact with the RIG and adjusts automatically with the trailer float motion to ensure proper engagement at all times. After loading is complete, the operator presses the Release button, lowering the PowerStop unit to a safely stored position, releasing the trailer.

SAFETY FEATURES

- RIG sensor bar notifies the operator if the restraint is not securely engaged to the trailer's Rear Impact Guard
- Automatic light sequencing with interior/exterior red/green lights always in opposition
- Full communication package with lights, signs and control panel with universal signage pictures for additional communication safety
- Integrated iDock® Controls for safe leveler interlock
- Restraining force in excess of 32,000 lbs.



Push-button operation to raise the restraint and engage the Rear Impact Guard.

LIGHT COMMUNICATION

The PowerStop restraint uses iDock® Controls with an LED 3-color light communication system. As a truck approaches, the exterior light is green and the interior light is red. Once the trailer is restrained, the interior light changes to green and exterior light to red, warning the driver not to pull away from the dock. When the trailer is released and the restraint hook is safely stored, the lights revert back to a green exterior and red interior. An interior amber Caution light is used if needed for bypass mode or faults.

CONSTRUCTION

The durable zinc-plated, steel housing unit is designed to protect the self-contained motor and all internal components from any weather conditions.

The PowerStop vehicle restraint is engaged hyrdaulically and electrically. The motor is 1/10 HP TENV 115-volt, single phase, with a NEMA 4X control panel



POWERSTOP®

COMMON OPTIONS

Cantilever bracket with a requested projection
Custom interlock sequence with leveler and/or door
Integrated control panel
Limit switches for door interlock
Remote power pack inside pit or inside building
Optional mounting hardware for wall or ground

W194N11481 McCormick Dr. | Germantown, WI 53022 dlmdocks.com | sales@dlmdocks.com 800-643-5424



dlmdocks.com

Designed, Engineered, and Manufactured in the U.S.A.
© 2024 Systems, LLC/DLM
Consistent with our policy of continuing product improvement, we reserve the right to change product specifications without notice or obligation.



Value Engineered

Dock Levelers